

simplebnf – A simple package to format Backus-Naur form*

Jay Lee[†]

2019/12/23

```
\bnfexpr \bnfannot
```

The `\bnfexpr` and the `\bnfannot` commands are simply wrappers around `\textttt` and `\textit`, respectively.

```
\begin{bnfgrammar}{\langle term \rangle} text \end{bnfgrammar}
```

The *term* argument of the `bnfgrammar` environment is the term to define a grammar. The text inside the environment should be a comma-separated list of keypairs. Each keypair represents an alternative syntactic form of the *term* and its annotation, delimited with a colon(:).

A sample code and the result is shown below:

```
\begin{bnfgrammar}{\bnfexpr{v}}
  n: integer,
  $lambda$x.e: abstraction
\end{bnfgrammar}

\begin{bnfgrammar}{\bnfexpr{C}}
  \bnfexpr{}: hole,
  \bnfexpr{C\,e}: application 1,
  \bnfexpr{v\,C}: application 2,
  \bnfexpr{C\,+\\,e}: addition 1,
  \bnfexpr{v\,+\\,C}: addition 2
\end{bnfgrammar}
```

$v ::= n \quad \text{integer}$ $ \quad \lambda x. e \quad \text{abstraction}$	$C ::= [] \quad \text{hole}$ $ \quad C e \quad \text{application 1}$ $ \quad v C \quad \text{application 2}$ $ \quad C + e \quad \text{addition 1}$ $ \quad v + C \quad \text{addition 2}$
---	--

*This file describes v0.0.1.

[†]E-mail: jaeho.lee@snu.ac.kr